

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# horo 33 / studio#21 st02 camouflage 04249 003



## IT

### codice doganale

55121990.

### utilizzo

tende, imbottiti, assorbimento acustico.

### caratteristiche

100% poliestere, altezza cm  $\pm$  140, peso  $\pm$  560 gr/m<sup>2</sup>.

### tintura

il prodotto è tinto in pezza.

### lunghezza pezze

circa 30 mtl., disponibile anche al taglio con maggiorazione.

### abrasione

> 40.000 cicli, ISO 12947-2.

### solidità alla luce

5, ISO 105 B02.

### solidità allo sfregamento

secco 4/5, umido 4, ISO 105 X12.

### resistenza alla cucitura

orlito 3 mm, trama 3 mm, ISO 13936-2.

### pilling

4/5, ISO 12945-2.

### resistenza al fuoco

1IM - UNI 9175; Classe 1 - UNI 9177;

Class 1 - EN 13773; EN 1021 part 1/2;

BS 7176 + A1 medium hazard; BS 5852 crib 5;

DIN 4102 - B1; NF-P 92 503 - M1;

NF-D 60 013 (AM 18); NFPA 260; NFPA 701 pass;

California TB 117:2013; IMO MED - Ftp 307 part 8;

ONCOM B 3825 - normal brennbar.

### attenzione

sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori.

consigliamo di verificare le schede tecniche di tutti i prodotti su [www.abitex.eu](http://www.abitex.eu)

## EN

### customs code

55121990.

### use

curtains, upholstered furniture, sound absorption.

### features

100% polyester, width cm  $\pm$  140, weight  $\pm$  560 g/m<sup>2</sup>.

### dyeing

piece dyed product.

### roll length

approx. 30 lm, can also be cut-to-length at an extra cost.

### abrasion resistance

> 40.000 rubs, ISO 12947-2.

### colour fastness to light

5, ISO 105 B02.

### fastness to rubbing

dry 4/5, wet 4, ISO 105 X12.

### seam slippage

warp 3 mm, weft 3 mm, ISO 13936-2.

### pilling

4/5, ISO 12945-2.

### fire resistance

1IM - UNI 9175; Classe 1 - UNI 9177;

Class 1 - EN 13773; EN 1021 part 1/2;

BS 7176 + A1 medium hazard; BS 5852 crib 5;

DIN 4102 - B1; NF-P 92 503 - M1;

NF-D 60 013 (AM 18); NFPA 260; NFPA 701 pass;

California TB 117:2013; IMO MED - Ftp 307 part 8;

ONCOM B 3825 - normal brennbar.

### attention

slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. please check the technical data sheets of all products on the abitex website [www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



sound  
absorbent



customize  
colors



printable



proposition  
65



year  
guarantee