

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# luci a san siro pois 09004



## IT

### codice doganale

58013700.

### utilizzo

imbottiti.

### caratteristiche

58% viscosa - 14% poliestere - 28% resina,  
altezza cm  $\pm$  140, peso  $\pm$  565 g/m<sup>2</sup>.

### tintura

il prodotto è tinta in filo.

### lunghezza pezza

circa 25 mtl.

### abrasione

>50.000 cicli, ISO 12947-2.

### solidità alla luce

4/5, ISO 105 B02.

### solidità allo sfregamento

secco 4, umido 3/4, ISO 105 X12.

### resistenza alla cucitura

ordito 1200 N, trama 900 N, ISO 13934-2.

### pilling

4/5, ISO 12945-2.

### resistenza al fuoco

11M - UNI 9175; EN 1021 1/2; BS 5852 part 1;  
BS 5852 crib 5; California TB 117-2013;  
IMO FTP Code 307 part 8.

### attenzione

sono ammesse leggere differenze di colore tra differenti  
partite.

## EN

### customs code

58013700.

### use

upholstered furniture.

### features

58% viscose - 14% polyester - 28% resin,  
width cm  $\pm$  140, weight  $\pm$  565 g/m<sup>2</sup>.

### dyeing

yarn dyed product.

### roll length

approx. 25 lm.

### abrasion resistance

>50.000 rubs, ISO 12947-2.

### colour fastness to light

4/5, ISO 105 B02.

### fastness to rubbing

dry 4, wet 3/4, ISO 105 X12.

### seam slippage

warp 1200 N, weft 900 N, ISO 13934-2.

### pilling

4/5, ISO 12945-2.

### fire resistance

11M - UNI 9175; EN 1021 1/2; BS 5852 part 1;  
BS 5852 crib 5; California TB 117-2013;  
IMO FTP Code 307 part 8.

### attention

slight colour differences between different batches are  
allowed.



fireproof



imo-med