

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

teraskin nappa 02359



IT
codice doganale
39100000.

utilizzo
imbottiti, medicale, outdoor.

caratteristiche
55% silicone - 45% poliestere, altezza cm \pm 137,
peso \pm 650 gr/m², spessore \pm 0,95 mm.

lunghezza pezza
circa 30 mtl., disponibile anche al taglio con maggiorazione.

abrasione
>130.000 cicli, ISO 12947-2.

solidità alla luce
7-8, ISO 105 B02.

solidità allo sfregamento
secco 4/5, umido 4, ISO 105 X12.

resistenza alla cucitura
ordito 3 mm, trama 3 mm, ISO 13936-2.

resistenza al freddo (e caldo)
-40°C (+ 200°C), ISO 17233.

sostenibilità
riciclabile, ecologico, sicuro per la salute, atossico,
esente da: solventi, PVC, PU, PFC, formaldeide, plastificanti,
ftalati, metalli pesanti, BPA, allergeni, additivi anti-batterici,
biocidi, sostanze ritardanti di fiamma.

resistenza al fuoco
1IM - UNI 9175; EN 1021 1/2; BS 5852 part 1;
BS 5852 crib 5; NF D 60 013;
California TB 117-2013; NFPA 260 Class 1;
IMO FTP Code 307 part 8; ÖNORM B 3825.

attenzione
sono ammesse leggere differenze di colore tra differenti
partite. consigliamo di verificare le schede tecniche di tutti i
prodotti su www.abitex.eu

EN
customs code
39100000.

use
upholstered furniture, medical, outdoor.

features
55% silicone - 45% polyester, width cm \pm 137,
weight \pm 650 g/m², thickness \pm 0,95 mm.

roll length
approx. 30 lm., can also be cut-to-length at an extra cost.

abrasion resistance
>130.000 rubs, ISO 12947-2.

colour fastness to light
7-8, ISO 105 B02.

fastness to rubbing
dry 4/5, wet 4, ISO 105 X12.

seam slippage
warp 3 mm, weft 3 mm, ISO 13936-2.

cold (and hot) crack resistance
-40°C (+ 200°C), ISO 17233.

sustainability
recyclable, eco friendly, safe for human health, non toxic, free
from: solvents, PVC, PU, PFC, formaldehyde, plasticizers,
phthalates, heavy metals, BPA, allergens, anti-bacterial
additives, biocides, flame retardant substances.

fire resistance
1IM - UNI 9175; EN 1021 1/2; BS 5852 part 1;
BS 5852 crib 5; NF D 60 013;
California TB 117-2013; NFPA 260 Class 1;
IMO FTP Code 307 part 8; ÖNORM B 3825.

attention
slight colour differences between different batches are
allowed. please check the technical data sheets of all
products on the abitex website www.abitex.eu



fireproof



imo-med



medical



outdoor



easy clean



eco-friendly