



**Centro Tessile Serico Sostenibile Srl**  
 via Castelnuovo, 3 - 22100 Como Italia  
 Pho +39 031 3312111/120 Fax: +39 0313312149  
 Amministrazione/Contabilità +39 031 3312102-154  
 P. IVA - C.F. 003900470133  
 Capitale sociale euro 600000,00 iv  
 mailbox@textilecomo.com  
 www.textilecomo.com



LAB N° 0045 L

Test Report No.:	<b>2103114-001</b>	Customer Code 07664
Date Test Report	<b>03-mag-21</b>	Dear:
Acceptance:	<b>2103114</b>	<b>ABITEX SRL</b>
Arrival date sample	<b>26-apr-21</b>	via del Cristo 84
Start date test	<b>26-apr-21</b>	33044 MANZANO (UD) Italia
End date test	<b>03-mag-21</b>	C.a. sig. Matteo Bortolossi
References:		Phone: +39 0432 746060
Sampling Mode:	Sampling by Customer *	

[C] Item:	<b>GANESHA - 02353</b>
[C] Declared Composition:	<b>65% Polyurethane - 29% Polyester - 6% Cotton</b>
[C] Typology:	<b>artificial leather</b>
[C] End use:	<b>upholstery</b>
Return:	<b>no requested</b>

### Test Results

Test	Method	U.M.	Result
<b>15066 UPHOLSTERY FURNITURE COMPONENTS: ASSESSMENT OF THE IGNITABILITY BY SMOULDERING CIGARETTE</b>	<b>NFPA 260:2019</b>		.
<b>Instrument:</b> Mini Mock Up Tester			
Test carried out on			cover fabric
Ignition source			SMOULDERING CIGARETTE
Materials of test assembly			
Upholstery filling: NON fire retardant polyurethane foam with a density of 28 kg/m <sup>3</sup>			
Inner cover: -			
Outer cover: SEE ARTICLE DESCRIPTION			
TEST RESULT			CLASS 1
Deviations from the method			none
Annex n.			1F
Details of the test results related to each specimen can be seen in the annex of this test report.			

(\*) = The tests marked in this way are not accredited by Accredia

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



**Centro Tessile Serico Sostenibile Srl**  
via Castelnuovo, 3 - 22100 Como Italia  
Pho +39 031 3312111/120 Fax: +39 0313312149  
Amministratore/Contabilità +39 031 3312102-154  
P. IVA - C.F. 003900470133  
Capitale sociale euro 600000,00 iv  
mailbox@textilecomo.com



LAB N° 0045 L

Test Report No.: **2103114-001**

Test	Method	U.M.	Result
------	--------	------	--------

**The Laboratory Manager**

Fausto Albonico

-----  
**END OF REPORT**  
-----

(\*) = The tests marked in this way are not accredited by Accredia

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



Centro Tessile Serico Sostenibile Srl  
Via Castelnuovo, 3 – 22100 Como Italia  
Tel. +39 031331211/120 Fax +39 031 3312149  
Amministrazione/Contabilità +39 031 3312102-154  
P.IVA – C.F. 03900470133  
Capitale sociale euro 600.000,00 iv  
mailbox@textilecomo.com  
www.textilecomo.com



LAB N° 0045 L

Annex n. 1F to test report n. 2103114-001

## DETAILS OF TEST RESULTS

### Test executed according to NPFA 260:2019 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture

Sample description: **GANESHA - 02353**

Declared composition: **65% Polyuerethane - 29% Polyester - 6% Cotton**

Conditioning of test specimen and ignition source: **21 ± 2,8 °C, <65% r.h.**

Testing temperature and r.h.: **20°C, 43% r.h.**

Filling specification: **NON FIRE-RETARDANT polyurethane foam with a density of 28 kg/m<sup>3</sup>**

Date of test: **03/05/2021**

Specimen number	1	2	3
Total combustion of the cigarette (YES / NO)	NO	YES	NO
Time of progressive smouldering from placement of the source (min)	5	24	7
Size of the damage in the vertical direction (mm)	15	12	13
Obvious ignition occurs (YES / NO)	NO	NO	NO
<b>CIGARETTE TEST RESULT (Class I/Class II)</b>	<b>Class I</b>	<b>Class I</b>	<b>Class I</b>

#### Cover Fabric Classification (ref. NFPA 260:2019)

##### **CLASS I**

When subjected to the cover fabric test, a specimen shall show no evidence of ignition of any test assembly. The vertical char on any of the three specimens shall not exceed 45 mm.

##### **CLASS II**

Cover fabrics that do not meet Class I criteria shall be designated as Class II.

*The following test result relate only to the ignitability of the combination of materials under the particular conditions of test. They are not intended as a means of assessing the full potential fire hazard of the material in use.*

*The probability that the criteria represent the truth observation is equal to 95%.*

*The expanded uncertainty is calculated by multiplying the combined standard uncertainty for a coverage factor  $k = 2$ , which for a normal distribution leads to a confidence level of approximately 95%.*

The Laboratory Manager  
Fausto Albionico