

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# b-green grs groviglio 04434



## IT codice doganale

54077300.

### utilizzo

imbottiti, assorbimento acustico.

### caratteristiche

48% poliestere - 52% poliestere riciclato,  
altezza cm  $\pm$  140, peso  $\pm$  720 gr/m<sup>2</sup>.

### tintura

il prodotto è tinta in pezza.

### lunghezza pezze

circa 25 mtl., disponibile anche al taglio con maggiorazione.

### abrasione

> 100.000 cicli, ISO 12947-2.

### solidità alla luce

4/5, ISO 105 B02.

### solidità allo sfregamento

secco 4, umido 4, ISO 105 X12.

### resistenza alla cucitura

ordito 2 mm, trama 3 mm, ISO 13936-2.

### pilling

4/5, ISO 12945-2.

### sostenibilità

oeko-tex; GRS.

### resistenza al fuoco

1IM - UNI 9175; EN 1021 part 1/2;

BS 7176 + A1 medium hazard; BS 5852 crib 5;

NF-D 60 013 (AM 18); NFPA 260 Class 1;

California TB 117:2013; IMO MED - Ftp 307 part 8.

### attenzione

sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. le schede tecniche vengono costantemente aggiornate sul sito, pertanto vi invitiamo a verificare online i dati del prodotto su [www.abitex.eu](http://www.abitex.eu)

## EN customs code

54077300.

### use

upholstered furniture, sound absorption.

### features

48% polyester - 52% recycled polyester,  
width cm  $\pm$  140, weight  $\pm$  720 g/m<sup>2</sup>.

### dyeing

piece dyed product.

### roll length

approx. 25 lm , can also be cut-to-length at an extra cost.

### abrasion resistance

> 100.000 rubs, ISO 12947-2.

### colour fastness to light

4/5, ISO 105 B02.

### fastness to rubbing

dry 4, wet 4, ISO 105 X12.

### seam slippage

warp 2 mm, welt 3 mm, ISO 13936-2.

### pilling

4/5, ISO 12945-2.

### sustainability

oeko-tex; GRS.

### fire resistance

1IM - UNI 9175; EN 1021 part 1/2;

BS 7176 + A1 medium hazard; BS 5852 crib 5;

NF-D 60 013 (AM 18); NFPA 260 Class 1;

California TB 117:2013; IMO MED - Ftp 307 part 8.

### attenzione

slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. as technical data sheets are updated from time to time, we invite you to verify the latest document published for each item on the website [www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



sound  
absorbent



recycled



standard  
100



year  
guarantee