

abitex

b-green grs groviglio petit tartan 04434 004

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu



IT
codice doganale
54077300.

utilizzo
imbottiti, assorbimento acustico.

caratteristiche
42% poliestere - 58% poliestere riciclato,
altezza cm \pm 140, peso \pm 720 gr/m².

tintura
il prodotto è tinta in pezza.

lunghezza pezza
circa 25 mt., disponibile anche al taglio con maggiorazione.

abrasione
> 40.000 cicli, ISO 12947-2.

solidità alla luce
3/4, ISO 105 B02.

solidità allo sfregamento
secco 4, umido 4, ISO 105 X12.

resistenza alla cucitura
ordito 2 mm, trama 3 mm, ISO 13936-2.

pilling
4/5, ISO 12945-2.

sostenibilità
oeko-tex; R.E.A.C.H.; GRS.

resistenza al fuoco
11M - UNI 9175; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NF-D 60 013 (AM 18); NFPA 260 Class 1;
California TB 117:2013; IMO MED - Ftp 307 part 8.

attenzione
sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. le schede tecniche vengono costantemente aggiornate sul sito, pertanto vi invitiamo a verificare online i dati del prodotto su www.abitex.eu

EN
customs code
54077300.

use
upholstered furniture, sound absorption.

features
42% polyester - 58% recycled polyester,
width cm \pm 140, weight \pm 720 g/m².

dyeing
piece dyed product.

roll length
approx. 25 m, can also be cut-to-length at an extra cost.

abrasion resistance
> 40.000 rubs, ISO 12947-2.

colour fastness to light
3/4, ISO 105 B02.

fastness to rubbing
dry 4, wet 4, ISO 105 X12.

seam slippage
warp 2 mm, weft 3 mm, ISO 13936-2.

pilling
4/5, ISO 12945-2.

sustainability
oeko-tex; R.E.A.C.H.; GRS.

fire resistance
11M - UNI 9175; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NF-D 60 013 (AM 18); NFPA 260 Class 1;
California TB 117:2013; IMO MED - Ftp 307 part 8.

attention
slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. as technical data sheets are updated from time to time, we invite you to verify the latest document published for each item on the website www.abitex.eu



fireproof



imo-med



sound
absorbent



recycled



OEKO
TEX®
standard
100