

abitex

horo

33

04249

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu



IT

codice doganale
55121990.

utilizzo

tende, imbottiti, assorbimento acustico.

caratteristiche

100% poliestere, altezza cm \pm 140, peso \pm 560 gr/m².

tintura

il prodotto è tinto in pezza.

lunghezza pezza

circa 30 mtl., disponibile anche al taglio con maggiorazione.

abrasione

> 100.000 cicli, ISO 12947-2.

solidità alla luce

5, ISO 105 B02.

solidità allo sfregamento

secco 4/5, umido 4, ISO 105 X12.

resistenza alla cucitura

ordito 3 mm, trama 3 mm, ISO 13936-2.

pilling

4/5, ISO 12945-2.

sostenibilità

oeko-tex.

resistenza al fuoco

1M - UNI 9175; Classe 1 - UNI 9177; Class 1 - EN 13773;
EN 1021 part 1/2; BS 7176 + A1 medium hazard;
BS 5852 crib 5; DIN 4102 - B1; NF-P 92 503 - M1;
NF-D 60 013 (AM 18); NFPA 260 Class 1;
NFPA 701 pass; California TB 117:2013;
IMO MED - Ftp 307 part 8; ÖNOM B 3825 - normal brennbar.

attenzione

sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. le schede tecniche vengono costantemente aggiornate sul sito, pertanto vi invitiamo a verificare online i dati del prodotto su www.abitex.eu

EN

customs code
55121990.

use

curtains, upholstered furniture, sound absorption.

features

100% polyester, width cm \pm 140, weight \pm 560 g/m².

dyeing

piece dyed product.

roll length

approx. 30 lm, can also be cut-to-length at an extra cost.

abrasion resistance

> 100.000 rubs, ISO 12947-2.

colour fastness to light

5, ISO 105 B02.

fastness to rubbing

dry 4/5, wet 4, ISO 105 X12.

seam slippage

warp 3 mm, weft 3 mm, ISO 13936-2.

pilling

4/5, ISO 12945-2.

sustainability

oeko-tex.

fire resistance

1M - UNI 9175; Classe 1 - UNI 9177; Class 1 - EN 13773;
EN 1021 part 1/2; BS 7176 + A1 medium hazard;
BS 5852 crib 5; DIN 4102 - B1; NF-P 92 503 - M1;
NF-D 60 013 (AM 18); NFPA 260 Class 1;
NFPA 701 pass; California TB 117:2013;
IMO MED - Ftp 307 part 8; ÖNOM B 3825 - normal brennbar.

attention

slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. as technical data sheets are updated from time to time, we invite you to verify the latest document published for each item on the website www.abitex.eu



fireproof



imo-med



sound
absorbent



customize
colors



printable



standard
100



10
year
guarantee