

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

luci a san siro arabesque 09014



IT

codice doganale

58013700.

utilizzo

imbottiti.

caratteristiche

66% viscosa - 11% poliestere - 23% resina,
altezza cm ± 140, peso ± 650 gr/m².

tintura

il prodotto è tinta in filo.

lunghezza pezza

circa 25 mtl.

abrasione

> 50.000 cicli, ISO 12947-2.

solidità alla luce

4/5, ISO 105 B02.

solidità allo sfregamento

secco 4, umido 3/4, ISO 105 X12.

resistenza alla cucitura

ordito 1200 N, trama 900 N, ISO 13934-1.

pilling

4/5, ISO 12945-2.

resistenza al fuoco

11M - UNI 9175; EN 1021 1/2; BS 5852 part 1;
BS 5852 crib 5; California TB 117-2013;
IMO FTP Code 307 part 8.

attenzione

sono ammesse leggere differenze di colore tra differenti
partite.

EN

customs code

58013700.

use

upholstered furniture.

features

66% viscose - 11% polyester - 23% resin,
width cm ± 140, weight ± 650 g/m².

dyeing

yarn dyed product

roll length

approx. 25 lm.

abrasion resistance

> 50.000 rubs, ISO 12947-2.

colour fastness to light

4/5, ISO 105 B02.

fastness to rubbing

dry 4, wet 3/4, ISO 105 X12.

seam slippage

warp 1200 N, weft 900 N, ISO 13934-1.

pilling

4/5, ISO 12945-2.

fire resistance

11M - UNI 9175; EN 1021 1/2; BS 5852 part 1;
BS 5852 crib 5; California TB 117-2013;
IMO FTP Code 307 part 8.

attention

slight colour differences between different batches are
allowed.



fireproof



imo-med